Figure 1a - UV Absorption of Combustion Gases



Figure 1b - UV Absorption of Nitrogen Based Gases



Figure 1c - Important Secondary Reactions

Oxidation

$O' + CO \Rightarrow CO_2$
$O' + NO \Rightarrow NO_2$
$O' + H_2O \Rightarrow 2OH$
$O' + NH_3 \Rightarrow NH_2' + OH$
$OH + CO \Rightarrow CO_2 + H$
$OH + CH_2O \Rightarrow H_2O + HCO$
$OH + NO \Rightarrow H + NO_2$
$OH + NO_2 \Rightarrow HNO_3$
$OH + NH_3 \Rightarrow NH_2' + H_2O$
$HCO + O_2 \Rightarrow HO_2 + CO$
$H + O_2 \Rightarrow HO_2$
$HO_2 + NO \Rightarrow OH + NO_2$
$HO_2 + CO \Rightarrow OH + CO_2$

Reduction

$NH_2' + NO \Rightarrow N_2 + H_2O$
$NH_2' + NO_2 \Rightarrow N_2 + H_2O_2$
$H + N_2O \Rightarrow N_2 + OH$
$H + NO \Rightarrow HNO$
$H + NO_2 \Rightarrow HNO_2$
$H + O_2 \Rightarrow HO_2$
$H + CO \Rightarrow HCO$



Figure 2a - Use of SUVR to Destroy Combustion Contaminants and/or VOC's



Figure 2b - Use of SUVR to Polish Residual NO_X and NH_3 Gases from an Upstream SNCR, SHR, or SCR Process

Figure 3a - SUVR to Control Combustion Contaminants and/or VOC's plus NO_X Emissions



Figure 3b - SUVR to Control NO_x Emissions





Figure 4a - Two Stage SUVR for Reducing NO_X Emissions



Figure 4b - Two Stage SUVR for Reducing NO_X Emissions



Figure 5 - Installation of the SUVR process on a Combustion Device to Remove NO_x and Residual NH_3 Emissions; Replacing the SCR Process

Figure 6 – Ammonia Sources for Exicited State Amidogen Radical (NH_2^*) Generation



4/24



Figure 7 - (Prior Art) SCR on Gas Turbine Waste Heat Recovery Boiler



Figure 8 - SUVR on a Gas Turbine Waste Heat Recovery Boiler



Figure 9b



Figure 9a



Figure 9 - Demonstration of the SUVR Process using a UV Laser or Electron Beam for Activation

12/24



Figure 10 - Relative Transmission Path Lengths of UV lines from a low Pressure Mercury Vapor Lamp

Figure 10a





Figure 11a - Use of SUVR to Polish Residual NO_X and NH_3 Gases in a Wet Electrostatic Precipator for Sulfate and Nitrate Salts and Ash



Figure 11b - Use of SUVR to Polish Residual SO_3, NO_X and NH_3 Gases from an Upstream Electron Beam System to Boost Efficiency to over 99%



Figure 12 - Electrostatic Field Protection of Ultraviolet Bulbs in Dirty Exhaust Gases



Figure 13 - Electrostatic Field + Boundary Layer of Clean Gas Protection of Ultraviolet Bulb in Very Dirty Exhaust Gases



Figure 14 a



Figure 14 b



Figure 14 c



Figure 14 d

Figure 14 - Amidogen Radical (NH_2*) Generators



Figure 15a



Figure 15 - Demonstration of ammonia gas mixing with lance or wall nozzle injection

Figure 16



Figure 16 - Demonstration of ammonia gas mixing with a Venturi Plate



Figure 17 - Installation of the SUVR process on a hot exhaust stack using the vaporization of water to cool the exhaust gases and the thermal decomposition of urea to supply the ammonia

4/1/24



Figure 18a



Figure 18b

Fuel based free radicals generated with the addition of 1-2% air or 1-4% water vapor added to fuel then exposed to ultraviolet light, dielectric barrier discharge, electron beam, or laser discharge.

Liquid Fuel requires longer residence time and higher water vapor content to promote gasification of liquid without coking. Reformer generated hydrogen gas can also be used to dilute liquid fraction.

Care must be taken to generate free radicals close enough to burner tip to prevent significant recombination before flame front



Figure 18c

Oxygen based free radicals generated with the addition of 1-3% water vapor added to air then exposed to ultraviolet light, dielectric barrier discharge, electron beam, or laser discharge.

Figure 18 - Use of SUVR at burner to reduce VOC emissions, Increase Flame speed, and reduce NOx emissions



Figure 19 - Organic Compound Destruction Using SUVR with Optional Halogen Acid Removal



Figure 20 - Portable SUVR unit for Organic Compound Destruction

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☑ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.
As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.